

FOIF

JP210(G) JP220(G) ROTATING LASER



JP210(G)/JP220(G) ROTATING LASER

Main features



JP210(G)





JP220(G)

- Stable electronic self-leveling, wide self-leveling range and auto over range alarm
- Offering high precision horizontal laser plane and plumb line or vertical plane and horizontal line(Only JP220)
- Scanning function
- Slope function
- Safety laser class, red laser and green laser selectable
- Remote control

Specifications

		JP210	JP210G	JP220	JP220G
Accuracy	Horizontal	±20"		±20"	
	Vertical	/		±30"	
Levelling system		Electronic sensor		Electronic sensor	
Auto-leveling range		±5°		±5°	
Measuring range		Radius 250m		Radius 250m	
Rotating speed		2~600 rpm		2~600 rpm	
Scanning angle		10° /45° /75° /105°			
Slope		±5°			
Laser class		Class 2 IEC 60825-1			
Laser wave length		635nm(up)/650nm(down)	532nm(up)/650nm(down)	635nm(up)/650nm(down)	532nm(up)/650nm(down)
Laser plummet		±1mm/1.5m			
Water proof		IP54			
Operating temperature		-20 to +50°C	-10 to +50°C	-20 to +50°C	-10 to +50°C
Power supply		DC 4.8V--6V (Rechargeable Battery)			
Continuou operating time		Approx. 20 hours			
Dimension/Weight		135(L)×135(W) ×155(H)mm/1.8kg		135(L)×135(W) ×155(H)mm/1.9kg	
FJP10 Laser Sensor					
Detecting window		50mm (2.0 in)			
Detecting accuracy		Precision: ±1mm (±0.04 in) Normal: ±2mm (±0.08 in)			
Display and indication		LCD both sides, buzzer			
Power supply		DC9V alkaline battery			
Dimension/Weight		150(L) × 79(W) × 24(H)mm/0.2kg			
FJP20 Remote		Remote range: approx. 20m			



Suzhou FOIF Co.,Ltd.

TEL:+86 512 65224904
 FAX:+86 51265230619
 Http://www.foif.com.cn
 E-mail:internationalsales@foif.com.cn
 ADD: 4 KongFu Si Lane, Suzhou 215006, P.R. China



Local Dealer: