



**JP3**  
**JP30** AUTOMATIC ROTATING LASER  
**JP300**



**JP300**

# JP3/JP30/JP300 AUTOMATIC ROTATING LASER



**JP3**



**JP30**



**FJP10**

## Main features

### **JP30 and JP300**

These two electronic automatic levelings are reliable and easy to handle and are totally auto-controlled. Each can automatically offer high precision laser flat datum plane and plumb line or laser vertical datum plane and horizontal line, and laser slope as well. They have the function of auto alarm and so on. And with infrared remote control machine, then can be controlled all the functions of apparatus. Meanwhile, the JP300 have two work modes, the rotation mode and scan mode, and the scan mode can make a visible laser line for interior using, the user can select the laser line length. These apparatus are widely used in areas such as architecture construction, building construction, plaza construction, airport construction, road construction, giant equipment installation, elevator installation, large area ground level off and upholster. And also used together with bulldozer, scraper, and then accomplishes auto-construction.

### **JP3**

It offers high precision laser flat datum plane and has function of auto over range alarm and so on. It is widely used in architecture construction, building construction and indoors upholster.

## Main Specifications

Laser Level		JP3	JP30	JP300
Accuracy	Horizontal:	±20	± 10	± 10
	Vertical:	/	± 15	± 15
Auto-leveling range		±8	± 5 °	± 5 °
Measuring range		Radius 100m	Radius 150m	Radius 150m
Beam rotating range		100 ~ 500 rpm	2 ~ 600 rpm	2-600 rpm
Laser wave		635nm		
Operating temperature		- 20 ~ + 50 ( - 4 ~ + 122 )		
Power supply		DC 4.8V--6V (Rechargeable Battery)		
Continuous operating time		Approx. 22 hours	Approx. 22 hours	Approx. 22 hours
Dimension		156x250mm	170x230mm	155(L) × 155(W) × 175(H)mm
Weight (With batteries)		2.15Kg	3.5Kg	2.1Kg
<b>FJP10 Laser Sensor</b>				
Detecting Range		50mm (2.0 in)		
Detecting Accuracy		Precision: ± 1mm ( ± 0.04 in) Normal: ± 2mm ( ± 0.08 in)		
Display and indication		LCD both sides, buzzer		
Power supply		DC9V alkaline battery		
Auto-off time		10min		
Dimension		150(L) × 79(W) × 24(H)mm		
Weight		0.2Kg		



**Suzhou FOIF Co., Ltd.**

TEL: +86 512 65224904

FAX: +86 512 65230619

Http:// [www.foif.com.cn](http://www.foif.com.cn)

E-mail: [internationalsales@foif.com.cn](mailto:internationalsales@foif.com.cn)

